

Hydrocarbon management

HM 50

Guidelines for the cleaning of tanks and lines for marine tank vessels carrying petroleum and refined products

5th edition



HM 50
GUIDELINES FOR THE CLEANING OF TANKS AND LINES FOR MARINE TANK
VESSELS CARRYING PETROLEUM AND REFINED PRODUCTS

Fifth edition

October 2018

Published by
Energy Institute, London

The Energy Institute is a professional membership body incorporated by Royal Charter 2003
Registered charity number 1097899

The Energy Institute (EI) is the chartered professional membership body for the energy industry, supporting over 20 000 individuals working in or studying energy and 250 energy companies worldwide. The EI provides learning and networking opportunities to support professional development, as well as professional recognition and technical and scientific knowledge resources on energy in all its forms and applications.

The EI's purpose is to develop and disseminate knowledge, skills and good practice towards a safe, secure and sustainable energy system. In fulfilling this mission, the EI addresses the depth and breadth of the energy sector, from fuels and fuels distribution to health and safety, sustainability and the environment. It also informs policy by providing a platform for debate and scientifically-sound information on energy issues.

The EI is licensed by:

- the Engineering Council to award Chartered, Incorporated and Engineering Technician status, and
- the Society for the Environment to award Chartered Environmentalist status.

It also offers its own Chartered Energy Engineer, Chartered Petroleum Engineer, and Chartered Energy Manager titles.

A registered charity, the EI serves society with independence, professionalism and a wealth of expertise in all energy matters.

This publication has been produced as a result of work carried out within the Technical Team of the EI, funded by the EI's Technical Partners. The EI's Technical Work Programme provides industry with cost-effective, value-adding knowledge on key current and future issues affecting those operating in the energy sector, both in the UK and internationally.

For further information, please visit <http://www.energyinst.org>

The EI gratefully acknowledges the financial contributions towards the scientific and technical programme from the following companies

Andeavor	Phillips 66
Apache North Sea	Qatar Petroleum
BP Exploration Operating Co Ltd	Repsol Sinopec
BP Oil UK Ltd	RWE npower
Centrica	Saudi Aramco
Chevron North Sea Ltd	Scottish Power
Chevron Products Company	SGS
Chrysaor	Shell UK Oil Products Limited
CLH	Shell U.K. Exploration and Production Ltd
ConocoPhillips Ltd	SSE
DCC Energy	TAQA Bratani
EDF Energy	Total E&P UK Limited
ENI	Total UK Limited
E. ON UK	Tullow Oil
Equinor	Uniper
ExxonMobil International Ltd	Valero
Innogy	Vattenfall
Kuwait Petroleum International Ltd	Vitol Energy
Nexen CNOOC	Woodside
Ørsted	World Fuel Services
Perenco	

However, it should be noted that the above organisations have not all been directly involved in the development of this publication, nor do they necessarily endorse its content.

Copyright © 2018 by the Energy Institute, London.
The Energy Institute is a professional membership body incorporated by Royal Charter 2003.
Registered charity number 1097899, England
All rights reserved

No part of this book may be reproduced by any means, or transmitted or translated into a machine language without the written permission of the publisher.

ISBN 978 0 85293 982 6

Published by the Energy Institute

The information contained in this publication is provided for general information purposes only. Whilst the Energy Institute and the contributors have applied reasonable care in developing this publication, no representations or warranties, express or implied, are made by the Energy Institute or any of the contributors concerning the applicability, suitability, accuracy or completeness of the information contained herein and the Energy Institute and the contributors accept no responsibility whatsoever for the use of this information. Neither the Energy Institute nor any of the contributors shall be liable in any way for any liability, loss, cost or damage incurred as a result of the receipt or use of the information contained herein.

Hard copy and electronic access to EI and IP publications is available via our website, <https://publishing.energyinst.org>.

Documents can be purchased online as downloadable pdfs or on an annual subscription for single users and companies.

For more information, contact the EI Publications Team.

e: pubs@energyinst.org

CONTENTS

	Page
Foreword	6
Acknowledgements	7
1 Introduction and scope	8
2 Tank cleaning guidelines	9
2.1 General information	9
2.1.1 Introduction and cleanliness standards	9
2.1.2 Inert gas	9
2.1.3 Static electricity	9
2.2 Bottom and line flushing	10
2.2.1 General	10
2.2.2 Fuel oil cargoes	10
2.3 Elimination of water for critical cargoes	10
2.4 Disposal of residues	11
2.4.1 Cargo residues	11
2.4.2 Scale and solid residues	11
2.5 Tank washing	12
2.5.1 General	12
2.5.2 After black oil cargoes	12
2.5.3 After white oil/clean product cargoes	13
2.5.4 After crude oil cargoes	13
2.5.5 After vegetable oil cargoes	13
2.5.6 After fatty acid methyl ester (FAME) or blended biodiesel cargoes	14
2.5.7 After gasoline/ethanol blended cargoes	14
2.5.8 Use of chemicals	14
2.5.9 Cleaning of sampling equipment and stilling wells	14
2.6 Tank inspections	15
2.6.1 General	15
2.6.2 Inerted tanks	15
2.7 Heating coils	15
2.7.1 Testing	15
2.7.2 Heating coils made from copper-containing alloys	15
2.8 Tank coatings	16
2.8.1 Temperature restrictions	16
2.8.2 Coating compatibility	16
2.8.3 Stainless steel	16
2.8.4 Coating condition	17
2.9 Cargo lines	17
2.9.1 General	17
2.9.2 Cargo compatibility	17
2.9.2.1 Liquid compatibility	17
2.9.2.2 Vapour compatibility	17
2.9.3 Testing of cargo lines and valves	18
2.10 Tank cleaning	18

Contents continued

	Page
2.11 Comments on individual cargoes (cargo types)	19
2.11.1 Naphthas and light distillate feedstocks (and/or – clean condensate, feedstocks, straight run benzene, pentane, natural gasoline, straight run gasoline)	19
2.11.2 Aviation gasoline (and/or – avgas, aviation spirit) and wide cut jet fuel, JP4, Jet B).	19
2.11.3 Leaded motor gasoline (and/or – premium/regular motor spirit, motor gasoline, mogas)	20
2.11.4 Unleaded motor gasoline (and/or – unleaded motor spirit, regular unleaded, premium unleaded, super unleaded, toluene, methyl tertiary butyl ether (MTBE), reformate, alkylate, cracked spirit, ethanol, motor spirit/gasoline blending components)	20
2.11.5 Ultra low sulfur gasolines	20
2.11.6 Solvents (and/or – special boiling point solvents, rubber solvent, unleaded cleaning spirit, white spirit)	20
2.11.7 Aviation jet fuel (and/or – aviation kerosene, dual purpose kerosene, Jet, Jet-A1, Avtur, ATK, JP5, JP8, synthetic jet fuel)	21
2.11.8 Premium and regular kerosenes (and/or – kerosene feedstock, burning oil, stove oil)	22
2.11.9 Gas oil and automotive diesel fuel (and/or – automotive gas oil, automotive diesel oil, DERV, extra light fuel oil, distillate marine diesel). . .	22
2.11.10 Ultra low sulfur automotive diesel fuel (and/or – ULSD, ULS turbine gas oil, LS marine gas oil, ULS diesel)	23
2.11.11 Crude oil and condensate	23
2.11.12 Base lubricating oils	23
2.11.13 Vacuum gas oil (and/or – cracker feed, waxy distillate)	23
2.11.14 Medium and heavy fuel oils	24
2.11.15 Low sulfur fuel oil (and/or – low sulfur atmospheric residue (LSAR), low sulfur waxy residue (LSWR))	24
2.11.16 Light fuel oil.	24
2.11.17 Gas to liquids (GTL) products	24
2.11.18 FAME and blended biodiesel	24
2.11.19 Light cycle oil (LCO)	25
 Annexes	
Annex A Glossary of terms	28
Annex B References.	31

LIST OF TABLES

Table	Page
Table 1 Tank cleaning recommendations	26

FOREWORD

The Energy Institute (EI) Hydrocarbon Management Committee is responsible for the production and maintenance of standards and guidelines covering various aspects of static and dynamic measurement of petroleum. The Hydrocarbon Management Subcommittee 4 (HMC-4) deals primarily with the measurement and loss of crude oil and oil products, focusing in particular on transport in the marine environment.

HMC-4 is made up of experts from the oil industry, cargo inspectors, ship owners and representatives from marine terminals. It is a truly international panel with representatives from most Western European countries, the Middle East, Far East and North and South America. Equipment manufacturers and experts with specific knowledge of measurement techniques are regularly invited to present papers to the committee.

The EI maintains liaison with parallel working groups of the American Petroleum Institute's (API) Committee on Petroleum Measurement, and other organisations concerned with quantitative measurement in other countries and in other industries. The API is a permanent invitee to meetings of the HMC-4 committee.

The EI Hydrocarbon Management guidelines (formerly Petroleum Measurement Manual and Petroleum Measurement papers) are widely used by the petroleum industry and have received recognition in many countries by consumers and the authorities. In order to promote international good practice the EI works via the British Standards Institute to develop standards through the International Standards Organization's technical committee TC-28 Petroleum Products and related products of synthetic or biological origin and its subcommittee TC28/SC2 Measurement of petroleum and related products.

A full list of Hydrocarbon Management guidelines is available on request from the EI. The EI Hydrocarbon Management guidelines are recommended for general adoption but should be read and interpreted in conjunction with safety, environmental, weights and measures, customs and excise and other regulations in force in the particular country in which they are to be applied. Such regulatory requirements have precedence over corresponding clauses in the EI document except where the requirements of the latter are more rigorous, when its use is recommended. Users should also consider contractual constraints imposed by charterers, cargo owners, ship owners and any other interested party.

Although it is believed that adoption of the recommendations of this guideline will assist the user, the EI cannot accept any responsibility, of whatsoever kind, for damage or alleged damage arising or otherwise occurring on vessels or in or about premises where this document has been applied, as final responsibility for adequate preparation of the vessel to receive a cargo lies with the parties controlling this task.

Users of these guidelines are invited to send comments, suggestions, or details of relevant experience to:

Technical Department, Hydrocarbon Management
Energy Institute
61 New Cavendish Street
London
W1G 7AR
United Kingdom
e:technical@energyinst.org

ACKNOWLEDGEMENTS

Members of the EI Hydrocarbon Management Committee 4 have been associated with the production of these guidelines. Membership at the time of publication is as follows:

Bazan Group (Oil Refineries Limited)
BP Oil International Ltd
ConocoPhillips Company
CEPSA
Chevron Products Company
China International United Petroleum & Chemicals Co. Ltd (Unipecc)
Chinese Petroleum Corporation
CITGO Petroleum Corporation
ENI Trading and Shipping
Essar Oil UK
ExxonMobil Refining and Supply Company
GALP Energia
Koch Supply and Trading
Marathon Petroleum Company
Mercuria
Monroe Energy
Petrobras
Petroineos
Phillips 66 Limited
PMI Pemex
PREEM AB
Qatargas
Repsol
Saras SpA
Saudi Aramco
Shell
Statoil
Sumed
Total
Valero Marketing and Supply Company

The International Federation of Inspection Agencies provided support via the working group.

Aviation Fuel Management issues have been reviewed by the Joint Inspection Group (JIG) Product Quality Committee whose contribution is also appreciated.

The guidelines were compiled by Melderley Consultants Limited.

1 INTRODUCTION AND SCOPE

This publication has been compiled with the aim of sharing the experiences of oil companies and other bodies represented on the HMC-4 with other branches of the oil industry, by providing guidance with regard to cleaning and washing of tanks on board petroleum tank vessels, particularly when carrying refined products and changing from one product to another.

Although the guidelines are written principally for seagoing ships they may also be applied to inland barges.

This document addresses issues relating to most classes of refined product but does not cover chemicals or gases.

Guidelines for crude oil washing are contained in HM 40 *Guidelines for the crude oil washing of ships' tanks and the heating of crude oil being transported by sea*, published by the EI.

Instructions regarding washing are normally issued by the charterers or vessel owners either in the form of a specific instruction or a general tank cleaning guideline provided on board. This publication is intended to provide additional guidance to those involved with issuing such instructions and to other parties who may be involved in confirming that suitable procedures have been followed.

This publication has been prepared primarily with the aim of maintaining product quality through the use of minimum effective tank washing procedures.

Further information relating to handling and quality of aviation fuels can be found in EI/JIG 1530 *Quality assurance requirements for the manufacture, storage and distribution of aviation fuels to airports*.

Safety and environmental issues are paramount in the operations described and for detailed guidance on these issues the latest revisions of ISGOTT, ISGINTT, MARPOL and SOLAS regulations should be referred to and will take precedence over any recommendations made here.

Nothing in the guidance contained in these guidelines suggests or encourages deviation from the carriage and cleaning requirements required by MARPOL Annex II Noxious Liquid Substance (NLS) regulations. MARPOL Annex II elevates the carriage and cleaning standards for specific cargoes. The cleaning standards, carriage requirements and slop disposal provisions of MARPOL are developed to protect the environment, not necessarily to prepare a tank for the next cargo. Products addressed in these guidelines to which Annex II NLS regulations may apply include but are not limited to: biodiesels, lube additives, toluene, methanol, MTBE, all vegetable oils, and many gasoline blending components.

This fifth edition removes references to aviation turbine gasoline and includes notes regarding the sensitivity of chemical grade naphtha to oxygenates. Table 1 now suggests requesting special cleaning instructions when loading gas oil after crude oil cargoes – cleaning code 'X'.

2 TANK CLEANING GUIDELINES

2.1 GENERAL INFORMATION

2.1.1 Introduction and cleanliness standards

Tank cleaning is carried out to:

- Prepare tanks for the carriage of the next cargo.
- Prevent the build-up of oily residues.
- Facilitate gas-freeing and tank entry for repairs/tank mopping.
- Comply with charter party requirements.
- Comply with MARPOL regulations.
- In extreme circumstances, prepare tanks for the carriage of clean ballast.

Cleaning can be accomplished by means of portable or fixed tank washing machines, or sometimes a combination of both using hot, cold, fresh or sea water and/or tank cleaning chemicals singly or in combination.

In order to reduce unnecessary bunker consumption, impact on the environment and associated costs, vessels should only tank clean when necessary. Also, introducing water into the cargo system is not always the best action as it can increase contamination if tanks and lines are not properly cleared.

Cargo tanks should be cleaned to the standard necessary to meet the requirements for the next cargo or, where applicable, for clean ballast or for tank entry and repairs. The tank cleaning Table 1 is to be used as a guide to the degree of cleaning necessary between cargoes.

Depending on the intended use of the product concerned, the standard of cleanliness required by some charterers/receivers may be different from that found within these guidelines. It is therefore extremely important to ensure that cleaning recommendations are provided in writing. Any deviations from recommendations should be confirmed in writing.

2.1.2 Inert gas

The inert gas system, where fitted, should be operated appropriately during tank washing, gas-freeing and tank preparation operations. Additional safety precautions should be taken for vessels which do not have inert gas systems, although the tank washing recommendations provided in this document still apply. Safety recommendations contained in ISGOTT should be followed.

Inert gas systems and scrubbers which are not operated correctly or are poorly maintained can result in cargo contamination with water, soot, SO₂ or SO₃. For aviation jet fuel cargo this can lead to filtration issues and reduce the effectiveness of static dissipators.

2.1.3 Static electricity

Precautions to prevent static discharge during washing operations should be followed at all times. These are detailed in ISGOTT.

Particularly hazardous conditions may exist when washing under non-inert conditions or when using hot water wash which can increase the temperature of cargo residues closer to their flashpoint.

2.2 BOTTOM AND LINE FLUSHING

2.2.1 General

It may be acceptable to flush the tank bottoms with the next grade to be loaded. This flushing medium is normally then discharged ashore or segregated on board. Discharges to shore can only take place after discussion with all parties involved. There will be costs associated with this procedure (in particular the flushing medium), and all parties will need to agree to these costs and how they are to be met.

Flushing pumps and lines using water can only be considered when suitable reception facilities are available ashore or where washings can be pumped to a suitable slops tank. On completion, all lines and pumps should be well drained, but the practice of draining to the pump room bilge should be avoided.

2.2.2 Fuel oil cargoes

When changing from a higher quality product to a lower quality product (e.g. high to low sulfur), it may be possible, under certain circumstances, to reduce the tank preparation procedures. In these cases, the amount remaining on board (ROB) should still be minimised.

Provided that any contamination would not adversely alter the quality of the cargo to be loaded, then load on top may be possible. However, this matter should always be clarified with, and agreed to by, all interested parties. Where uncertainty exists, the tank washing guidelines should be followed.

When loading vacuum gas oil/waxy distillate or other feedstock products, it will be necessary to remove salt residues from any tank which has previously contained salt water ballast or has been cleaned using salt water (see Table 1), typically using a fresh water rinse.

2.3 ELIMINATION OF WATER FOR CRITICAL CARGOES

When it is necessary to mop tanks dry for critical cargoes such as aviation kerosene, lubricating oil, or FAME, care should be taken to achieve a compatible standard of preparation throughout that portion of the cargo system allocated to the critical product. The following procedures should be followed:

The cargo lines which are to load and discharge the critical product should be opened and well drained. This includes manifolds, drop lines, pump discharge lines and tank suction lines.

Cargo pumps and their associated air vessels, strainers and bypasses should be opened and well drained. This is to include any vacuum breakers.

Individual tank suction valves should be opened and remain open during the mopping process. Valve inspection covers should be opened as necessary.

Where fitted, fixed eductor systems should be blown through with air, valves opened and lines left to drain into the tank prior to mopping.

Fixed tank washing lines should be drained, and any water in the leg between the main line and the machine allowed to drain into the tank via the machine prior to mopping.

After draining, the fixed tank cleaning machines should be positively isolated from the supply line by blanking or other secure means.

Particular attention should be paid to the inert gas deck seal overboard line. It should be ascertained that this line is free from blockage and that there are no valves partially or fully closed. Any substantial increase in the deck seal water level will cause 'carry over' and introduce water back into the tank during reinerting.

Low point drains on inert gas lines should be cleared of water and other liquid contamination. Condensed liquids in the inert gas lines can be hazardous.

As a general rule when loading, the product should be directed initially into a single tank using as many lines as possible. This will ensure that any water trapped in the system will be flushed through to this single tank. The water is then much easier to deal with at the discharge port if necessary. However, this procedure should be verified with the charterers.

2.4 DISPOSAL OF RESIDUES

2.4.1 Cargo residues

Ballast residues remaining on crude oil and black oil carriers should be retained on board. Vessels loading crude oil may load on top of these residues provided they receive permission from the cargo owner or charterer. Black oil carriers should discharge the residues to shore reception facilities, when they are available; otherwise, they should retain them on board, segregated from the cargo, until such times as it is possible to either load on top or discharge to a shore facility.

Residues should be dealt with in compliance with current MARPOL regulations to reduce the quantity of residues on board. When shore reception facilities are available at the loading port, residues should be discharged to the facilities. If they are not available, residues should be retained on board, segregated from the cargo.

2.4.2 Scale and solid residues

Scale and solid residues on the horizontal surfaces within a tank can contain volatile liquids and generate gas when disturbed. On crude oil carriers the build-up of sludge deposits can be controlled by effective crude oil washing. On other ships, routine water washing can be used. When sludge has to be physically removed from tanks, it shall not be disposed of overboard at sea but should be bagged, accurately labelled and landed to shore reception facilities. In coated tanks scale should be minimal, unless significant coating breakdown occurs.

2.5 TANK WASHING

2.5.1 General

Appropriate stern trim and efficient use of washing equipment are important. Minimum tank washing patterns should be used. Any accumulations of scale should be removed frequently, and excessive coating breakdown leading to build-up of scale should be recorded.

2.5.2 After black oil cargoes

These cargoes range from gas oils to heavy fuel oils and the degree of cleaning will vary considerably with the grade to be loaded and the grades previously carried. Products within this group are persistent oils and residues and should be handled in accordance with 2.4.

If the ship is reloading at the discharge port, it may be possible to pump washings/residues from tank cleaning operations to a shore facility. Otherwise, the residues will be retained on board. Regardless of the medium used for washing (cargo or water), care should be taken to ensure that segregation is not compromised.

Heavy fuel oils may leave residues on tank bottoms and structures at low temperatures and these can cause serious contamination of the lighter fuels and gas oils. Washing should be continued until the required degree of cleanliness is achieved. The bottom portion of the tank, together with any internal structure, may require particular attention, especially after carrying heavy or waxy fuel oils. Where available, portable tank cleaning machines may be required to ensure adequate coverage.

Hot water should always be used when the nature of the cargo warrants it or when a special degree of cleaning is required. The temperature of any residues should be at least 15 °C above the pour point in order to achieve effective removal by tank washing.

Scale formation is not usually heavy in ships which are employed solely on black oil trading, but where present it may be mixed with waxy deposits from fuel oils, which make it difficult to clean to the standard for gas oils and light fuel oils, etc. If a build-up occurs special arrangements may need to be made to remove or reduce these deposits.

The amount of washing required when changing from a black oil cargo to a white oil cargo cannot be defined precisely, as it varies considerably and depends primarily on the length of time the vessel was in the black oil trade, the condition of the tank coating and the arrangement of the cleaning machines within the tanks. In the best of situations it might take as little as four hours per tank; however, under less than ideal circumstances it can take many times longer. It is particularly important to ensure that blind areas under structures are adequately washed.

After the initial washing, the tank should be gas-freed and inspected to check on the effectiveness of the washing.

One of the major causes of tanks not being washed properly is poor monitoring of machines. They are prone to sticking, so that the nozzles fail to rotate in the vertical plane and the body fails to rotate in the horizontal plane. This results in the majority of the structure being washed only by splashing. Poor washing may also be caused by poor stripping – failure to remove water from the tank during the wash. This can be due to a number of factors, including insufficient trim, adverse list, or the pumps not keeping up with the water being added to the tank.

2.5.3 After white oil/clean product cargoes

White oil cargoes range from very light volatile oils like naphtha, to gas oils and lubricating oils.

Cold water washing is generally adequate for cleaning after most white oil cargoes, except after the carriage of the heavier lubricating oils where hot water or chemical wash may be required. Also, the risk of contamination of certain grades may require the removal of all previous cargo (see Table 1).

Although it is often important to remove all traces of the last cargo, it is also important to avoid excess tank washing, particularly with hot water, as this may eventually lead to expensive renewal of tank coatings. Providing that the coatings are in a good condition, adhesion of most types of clean oil is minimal and this reduces the amount of washing required.

With volatile cargoes, little residue is left on tank sides and structure other than liquid and gases trapped in scale and other loose materials. With gas oils and lubricating oils an oily film will remain. With all cargoes, there is also a small amount of liquid left below the effective stripping level.

2.5.4 After crude oil cargoes

The statutory requirements for washing after crude oils are contained within MARPOL. Additional sources of information are the vessel's cargo operations manual and EI HM 40.

The following points should be assessed when considering the need for water washing of crude oil tanks:

- the build-up of sludge in the tanks;
- wax content of the crude;
- the possibility of delaying the washing until the vessel is in warmer water;
- the use of portable machines, and
- the next crude to be carried and its suitability for washing.

2.5.5 After vegetable oil cargoes

Vegetable oils can be defined as drying, non-drying and semi-drying.

Non-drying oils are liquid at ambient temperatures and are easy to clean from surfaces using detergents and degreasers. Iodine values tend to be below 110 (examples are coconut oil, palm oil, palm kernel oil, olive oil).

Semi-drying oils have iodine values between 110 and 140.

Drying oils create solid residues which can form a hard skin at ambient temperatures. They are more difficult to remove from surfaces. Iodine values tend to be between 140 and 190 (examples are linseed oil, tung oil).

The drying properties (iodine value) are not related to the melting point so a light oil may well exhibit drying properties.

There are many types of vegetable oil, some of which have chemical additives. Generally, efforts should be made to remove all traces of such cargoes before loading petroleum products, as vegetable oil traces may affect not only the next cargo but those following later.

Lighter vegetable oils will typically be cold water washed then washed with warm water and a degreaser or saponifier. Heavier types may require hot water washing, again with degreaser or saponifier, followed with a solvent wash. If the previous cargo was a drying oil, then a hot wash with saponifier followed by additional water washes until the pH is neutral will be required. Cold water washing of each tank immediately after completion of discharge may avoid formation of a film on internal tank surfaces and should be carried out before warm or hot water washes which may cause oil films to dry ('varnish') unless cold water is used first.

See also 2.5.6, 2.11.2 and 2.11.7 regarding loading aviation jet fuel and aviation gasoline cargoes after biologically-derived products.

2.5.6 After fatty acid methyl ester (FAME) or blended biodiesel cargoes

Analysis has shown that FAMEs adhere to surfaces more readily than other oils. However, as they remain liquid at ambient temperatures, they can be cleaned using a water wash and saponifier (type to be recorded in the vessel cleaning log) as described in 2.5.5 for lighter vegetable oils.

Contamination of aviation kerosene with FAME is a serious concern. Intermediate cargoes and a strict washing regime are therefore recommended when following these cargoes with aviation kerosene (see 2.11.7) and special cleaning instructions should be obtained from the cargo owner.

Note: The recommendations relating to FAME also apply to other fatty acid esters.

2.5.7 After gasoline/ethanol blended cargoes

For tank cleaning purposes these cargoes may be treated in the same way as the equivalent non-biologically-derived cargoes for non-aviation fuel purposes. Where aviation products are involved, see 2.11.2 and 2.11.7

2.5.8 Use of chemicals

Due to environmental considerations, tank cleaning chemicals should no longer be used except where there is a requirement for stringent cleaning, in which case specific instructions should be issued for chemically-assisted cleaning at the time of the cargo nomination. Where chemicals are used, details should be recorded in the vessel cleaning log and slops should be segregated to allow for easier disposal.

Note: The use of saponifiers can cause haze in any hydrocarbon. Tank cleaning chemicals containing surfactants should not be used to prepare tanks for aviation jet fuel or aviation gasoline cargoes, as residues can cause fixed haze in the fuel and harm aviation fuel filters (see 2.11.7).

2.5.9 Cleaning of sampling equipment and stilling wells

The tight specifications for sensitive grades require extreme care during sampling, particularly closed or restricted sampling, to avoid contamination from previous cargoes or build-up of residues. Examples of this are FAME contamination of aviation fuels, and vegetable oils in gasolines. To reduce the possibility of drawing unrepresentative samples, the cleaning of sampling equipment, vapour locks, standpipes and stilling wells is recommended as part of the tank cleaning regime.

2.6 TANK INSPECTIONS

2.6.1 General

Responsibility for the cleanliness and overall suitability of tanks (including coating), lines and pumps to carry the nominated grades lies with the Master. Inspections are frequently carried out by the loading supervisors from the shore facility or by independent inspectors acting on behalf of the cargo owner. However, while such inspections may provide an opinion regarding those tanks which have been inspected, they do not relieve the Master of his/her responsibilities.

Tank entry for inspections is potentially dangerous and should only be done under close scrutiny in accordance with a strict permit to enter/work system in gas-free tanks. Careful attention should be given to the need for lighting, access, safety equipment, personal protective equipment and the general tank environment, e.g. residues on plates (slip hazard), etc.

2.6.2 Inerted tanks

Any requirement for cargo tank(s) to be gas-freed to allow internal inspection should be contained within the agreed charter party or voyage orders for the voyage about to be undertaken, as deinerting/reinerting is costly and time-consuming.

Reference should be made to ISGOTT recommendations with regard to inerting.

2.7 HEATING COILS

2.7.1 Testing

Heating coils should be pressure tested, and if necessary, blown through and repaired, on each occasion prior to:

- Loading a cargo which requires heating.
- Carrying out tank repairs or tank entry (so that any coil leak will not introduce hydrocarbon gases or product into the tank).
- Gas-freeing for voyage repairs or dry-docking.

Similar action should be taken when changing from a low flashpoint to a high flashpoint cargo or from black oil products to white oil products.

2.7.2 Heating coils made from copper-containing alloys

Heating coils made from copper-containing alloys can reduce the thermal stability of aviation kerosene due to copper dissolving into the cargo from the alloy.

Concentrations of copper in aviation kerosene fuel above 10 parts per billion (ppb) start to affect thermal stability and 50 ppb invariably results in failure to meet specified requirements.

For this reason, aviation kerosene shall not be carried in ships fitted with heating coils made from copper-containing alloys.

2.8 TANK COATINGS

2.8.1 Temperature restrictions

In ships with coated tanks, the temperature and pressure of washing water should not normally exceed 66 °C and 10,5 kg/cm² respectively. However, these may be increased subject to the following criteria:

Agreement from the coating manufacturer that excessive heat and/or pressure will not damage the coating.

Agreement from the tank cleaning equipment manufacturer that excessive heat or pressure will not cause damage to the machines.

The temperature of the washing water should always be at least 15 °C above the pour point of the previous cargo.

In coated tanks of white oil carriers, washing with cold water is generally adequate, except where more stringent cleaning is required after the carriage of vegetable oils, lubricating oils and diesel fuel. Hot water (and/or detergents) may be used occasionally to degrease tank structures, expedite gas-freeing for entry or where a gas-free condition is required for a major change of grade. When hot water is used this should be in accordance with these criteria.

2.8.2 Coating compatibility

Although not directly related to tank washing, it should be noted that tank coatings are not compatible with all products. Problems usually relate to chemicals rather than petroleum products, but manufacturers' resistance lists (usually kept on board) should be consulted if there are any doubts regarding coating compatibility.

Organic epoxy coatings can absorb some chemical cargoes, particularly chlorinated solvents. The contamination potential to subsequent cargoes (particularly aviation kerosene) may be considerable, as significant quantities can be absorbed and retained, depending on the chemical, exposure time, temperature, specific coating type, thickness, condition, etc. Contamination can persist after several subsequent cargoes and washings.

For aviation fuels, many oil companies have their own list of acceptable coatings. Cargo tanks with zinc silicate coatings or zinc silicate linings should not be used for transportation of jet fuel because of the potential adverse impact on fuel thermal stability. Where this is unavoidable, specialist advice should be sought regarding additional testing requirements, e.g. thermal stability testing at elevated temperatures prior to loading and discharge. The charterer should be consulted regarding coating acceptability for aviation fuel cargoes.

2.8.3 Stainless steel

Although stainless steel is compatible with most grades it is subject to attack by chlorinated compounds. This is made worse by the presence of water. Also, some stainless steel grades are subject to attack by sea water, so if a sea water wash is used in a stainless steel tank this should be followed immediately by a fresh water rinse.

Note: Some shore-supplied 'fresh' water can contain sufficient chlorine to attack/discolour stainless steel.

2.8.4 Coating condition

Damaged, flaking or blistering paint can increase hold-up of residues from previous cargoes, and tanks with damaged coating should be avoided, particularly for critical cargoes such as naphthas, light distillate feedstock and aviation kerosene.

2.9 CARGO LINES

2.9.1 General

Procedures for line washing should be contained in the vessel's cargo operations manual. Careful visual inspection of the actual pump room and above-deck piping configuration should be undertaken to identify any problem areas or 'dead ends' which will require special attention.

MARPOL pumps and lines should be included in all draining, cleaning and washing operations, which should be recorded in accordance with current MARPOL regulations.

2.9.2 Cargo compatibility

When loading more than one grade of cargo, it should be determined whether the grades are compatible in both the liquid and vapour state.

Compatibility between cargoes is entirely dependent on their essential characteristics and the quality specification of each grade. Pipeline admixture should be kept to a minimum at all times, as each admixture will result in some change in the quality of the loaded cargo. Permissible admixture of one cargo by another is governed by the tolerance of quality characteristics such as flashpoint, colour, sulfur content, viscosity, etc.

In general, admixtures may only be permitted for those loadings where wash code 1 is shown in Table 1.

2.9.2.1 Liquid compatibility

If the grades are not compatible, each grade should be loaded through a separate system, with segregation provided by two valves or a blind.

Where different but compatible cargoes, such as two grades of crude, are loaded, single valve segregation may be acceptable providing that the critical valves have been tested and proved tight.

If two or more cargoes are compatible, loading should be carried out in sequence, commencing with the most critical cargo. Any admixing which may occur should not adversely affect the quality of the second cargo to be loaded. Lines should be drained and/or stripped between grades.

2.9.2.2 Vapour compatibility

Vapours from a volatile cargo such as gasoline can be taken up in diesel or gas oil cargoes which share the same vent systems, or are under the same positive pressure of inert gas. If vapour mixing can occur, each cargo should be loaded on a separate cargo and vent system with vent system cross-over valves closed and tagged. If it is not possible to load using

separate vent systems then, when the ship design allows without impacting on latest SOLAS regulations, individual tanks should be isolated from the system.

Interconnecting inert gas block valves should be closed and tagged and if vapour contamination from slops is possible, slops should be isolated from the main inert gas line. The oxygen content of isolated slop tanks should be monitored to ensure that it remains less than 8 % by volume.

Note: Before any tank is isolated from the main venting system, due consideration should be given to meeting the SOLAS requirements and a formal risk assessment should be conducted. The pressure in any tank segregated from the main venting system should be carefully monitored to ensure that individual tank venting arrangements are adequate to prevent formation of vacuum or a build-up of pressure.

2.9.3 Testing of cargo lines and valves

On each occasion a tank is gas-freed and opened for entry, every effort should be made to pressure test the associated internal pipelines and valves. A brief inspection of coatings and fittings should be undertaken at the same time. On no account should cargo be used to test pipelines and valves. Only clean water should be used for this purpose.

2.10 TANK CLEANING

Table 1 provides guidelines for cleaning.

The table assumes that tanks are coated and in good condition. Where this is not the case additional cleaning may be required depending on the cargo involved; typically, the addition of gas-freeing, descaling and mopping where wash only is specified.

Stripping and draining following discharge or washing is assumed to be thorough, such that any liquid ROB is confined to the pump well (if present). All associated lines (suction, deck lines, and drop lines, etc.) are to be cleared and drained of all product or water.

Where washing is specified this includes deck lines, loading drop lines and cross-over lines.

The following of these guidelines does not necessarily mean that the tank(s) will be acceptable for the next intended cargo. The Master is ultimately responsible for the cleanliness of the tank(s) and should ensure that the end result meets the owner's/charterer's/shipper's expectation.

Consideration may be given to substituting mopping by enhanced stripping and drying where such facilities are available.

Note: The internal tank structure must be considered, as internal framing/ steam coils/ fixtures and fittings may affect the quantity of water or previous cargo ROB and may not allow the tank to be considered 'dry' even after additional stripping and drying.

2.11 COMMENTS ON INDIVIDUAL CARGOES (CARGO TYPES)

2.11.1 Naphthas and light distillate feedstocks (and/or – clean condensate, feedstocks, straight run benzene, pentane, natural gasoline, straight run gasoline)

Naphtha and light distillate feedstocks should not be contaminated by lead and should not be carried directly after cargoes that contained lead, e.g. aviation gasoline. Tank coating should be in good condition, as blistered or flaking tank coating can be a source of contamination from the previous cargo.

When loading after any cargo containing FAME a hot water wash may be needed to remove residues. Cargoes are generally water- and colour-critical.

Heavier feedstocks can tolerate minor admixing of aviation kerosene, kerosene, solvents or lighter feedstocks.

Sea water washing should be followed by a fresh water rinse to remove chlorides.

Chemical grade naphtha is very sensitive to contamination by oxygenates. Careful assessment is recommended and some contracts may specify that three oxygenate-free cargoes must be carried before loading this cargo.

2.11.2 Aviation gasoline (and/or – avgas, aviation spirit) and wide cut jet fuel, JP4, Jet B)

Aviation gasoline products may have a high lead content and are often dyed.

Uncoated tanks should be hot water washed and have any loose bottom scale removed before loading.

Water cannot be tolerated and extreme care should be taken to ensure that tanks and lines are drained before loading or discharging. Hand mopping is recommended. Products are also sulfur-critical.

Detergents and saponifiers should not be used to prepare tanks for aviation gasoline cargoes as residues can cause fixed haze in the fuel and harm fuel filters/coalescers.

Contamination of aviation gasoline with oxygenates (ethanol, MTBE, etc.) could lead to specification issues. Thorough washing is required to ensure prevention of cross-contamination and the proposed tank cleaning/flushing plan should be discussed and agreed with the charterer.

To avoid contamination from FAME it is recommended to have three intermediate cargoes with no FAME between FAME (B100) or any cargo with a FAME content greater than 15 % (B15) and an aviation gasoline cargo.

When following cargoes with a FAME content of 5 % or less (B5 or below), a hot water wash, including flushing of pumps and lines, followed by draining is recommended as a minimum.

When following cargoes with a FAME content of 15 % (B15) or less, but above B5, a hot water wash, including flushing of pumps and lines, followed by draining is again recommended as a minimum. However, tanks must be in good condition and washing needs to be particularly stringent. A single intermediate cargo with no FAME content is suggested as an alternative, followed by a hot water wash, including flushing of pumps and lines, and by draining.

The very low tolerance for FAME contamination requires extreme care during sampling. To reduce the possibility of drawing unrepresentative samples, consideration should be given to cleaning of standpipes and stilling wells as part of the tank cleaning regime when tanks have previously held cargoes containing FAME.

Note: The recommendations relating to FAME also apply to other fatty acid esters.

2.11.3 Leaded motor gasoline (and/or – premium/regular motor spirit, motor gasoline, mogas)

These products are often dyed and may contain surfactant additives.

Only minimal amounts of higher boiling point cargoes such as gas oil can be tolerated in motor gasoline. Depending on the product specification, up to 0,1 % volume may be tolerated. Where the product is close to specification limits a nil tolerance level will apply. Products are also sulfur-critical.

Tanks will require washing when following cargoes of dyed gas oil or kerosene. Uncoated tanks should be hot water washed and have loose bottom scale removed before loading.

2.11.4 Unleaded motor gasoline (and/or – unleaded motor spirit, regular unleaded, premium unleaded, super unleaded, toluene, methyl tertiary butyl ether (MTBE), reformate, alkylate, cracked spirit, ethanol, motor spirit/gasoline blending components)

Thorough tank washing is required when following leaded products, dyed gas oil or kerosene. Products are also sulfur-critical.

Uncoated tanks should be hot water washed and have any loose bottom scale removed before loading.

2.11.5 Ultra low sulfur gasolines

In addition to the comments in 2.11.4, these cargoes have a typical maximum sulfur content of 10 ppm (or possibly 50 ppm depending on location). If they are to be loaded into tanks or through lines that have previously contained cargoes that had a greater sulfur content, care should be taken to ensure that admixing is kept to a minimum.

These products are salt-water-critical as the high specifications will not allow sodium or potassium. Fresh water washing and mopping may be specified.

2.11.6 Solvents (and/or – special boiling point solvents, rubber solvent, unleaded cleaning spirit, white spirit)

These are volatile unleaded products.

Due to wide variations in specifications within grades, specific guidance should be sought on the allowable levels of admixing with other solvents.

Solvents are frequently odour-critical which can be a particular problem after gas oil cargoes. Common vapour lines should be considered for isolation for this reason.

No admixing with other types of product can be tolerated and these products should not be carried after leaded cargoes.

Uncoated tanks should be hot water washed and have any loose bottom scale removed before loading.

2.11.7 Aviation jet fuel (and/or – aviation kerosene, dual purpose kerosene, Jet, Jet-A1, Avtur, ATK, JP5, JP8, synthetic jet fuel)

Products are unleaded and fairly volatile.

Aviation jet fuel cargoes shall not be loaded on maiden voyages or on first voyages after a dry dock where modifications to cargo handling systems (tanks, pumps and lines) have taken place, due to the high risk of contamination.

Products may contain relatively high levels of sulfur which could affect the quality of a subsequent low sulfur cargo.

Aviation jet fuel should not be carried after leaded products.

Very tight specifications preclude admixing by other cargoes except undyed general purpose kerosenes with no biological components.

Water cannot be tolerated and extreme care should be taken to ensure that tanks and lines are drained before loading. Hand mopping is recommended.

Due to strict limitations on biological contamination, it is recommended to have three intermediate cargoes with no FAME between FAME (B100) or any cargo with a FAME content greater than 15 % (B15) and a subsequent aviation jet fuel cargo, and special cleaning instructions should be obtained.

When following cargoes with a FAME content of 5 % or less (B5 or below), a hot water wash, including flushing of pumps and lines, followed by draining is recommended as a minimum.

When following cargoes with a FAME content of 15 % (B15) or less, but above B5, a hot water wash, including flushing of pumps and lines, followed by draining is again recommended as a minimum. However, tanks must be in good condition and washing needs to be particularly stringent. A single intermediate cargo with no FAME content is suggested as an alternative, followed by a hot water wash, including flushing of pumps and lines, and by draining.

The very low tolerance for FAME contamination requires extreme care during sampling. To reduce the possibility of drawing unrepresentative samples, consideration should be given to cleaning of standpipes and stilling wells as part of the tank cleaning regime when tanks have previously held cargoes containing FAME. Where the FAME content of a previous cargo is not known it should be assumed to be 15 %.

Other cargoes can have a deleterious effect on aviation kerosene product quality and intermediate cargoes are recommended in these circumstances. Cleaning chemicals shall not be used to prepare tanks for aviation kerosene cargoes as residues can cause fixed haze in the fuel and harm aviation fuel filters.

In all cases salt contamination needs to be minimised after washing with sea water. A fresh water rinse is recommended following sea water wash but thorough mopping may suffice.

Note: The recommendations relating to FAME also apply to other fatty acid esters.

2.11.8 Premium and regular kerosenes (and/or – kerosene feedstock, burning oil, stove oil)

Products may contain relatively high levels of sulfur which could affect the quality of a subsequent low sulfur cargo.

Flashpoint may be critical such that admixing with low flashpoint cargoes in tanks and lines should be avoided.

Admixing of dyed kerosene with undyed kerosenes can result in the undyed cargo not meeting colour specifications. Tanks which have carried dyed products will require washing and mopping dry prior to loading undyed products.

Where dye is not a concern, these products will not require tanks to be mopped after water washing unless following lube oil or light fuel oil.

Small amounts of gas oil may be tolerated (up to 0,1 % volume), subject to comments under 2.11.9.

2.11.9 Gas oil and automotive diesel fuel (and/or – automotive gas oil, automotive diesel oil, DERV, extra light fuel oil, distillate marine diesel)

Some admixing with lighter distillate cargoes such as kerosene is acceptable, depending on minimum flashpoint requirements for the individual cargo. However, flashpoint requirements will preclude admixing with any naphtha, motor gasoline or other cargoes with low flashpoints.

Water contamination is a problem leading to 'haze' in the product. This can produce a water layer and subsequent corrosion in downstream storage. Sodium in any dissolved salt can lead to damage to blades if the fuel is used for gas turbines. Care should therefore be taken to ensure that water is removed from tanks, pumps and lines before loading. Uncoated tanks should be hot water washed and have any loose bottom scale removed before loading.

The admixing of dyed gas oil with undyed gas oil can result in the undyed material not meeting the colour specification and tanks which have carried dyed products will require washing prior to loading undyed products.

Saponifiers and degreasers can have a negative effect on gas oil or automotive diesel fuel quality and if these are used hot water washing is recommended to remove any traces.

Increasingly, diesel fuels for road transport are blends of FAME and conventional diesel fuel-blended biodiesel. These blends may simply be referred to as diesel fuel, but the grade name may indicate the percentage of FAME. Thus a B5 diesel fuel contains 5 % FAME and a B15 diesel fuel, 15 % FAME. Cleaning procedures vary with the percentage of FAME in the blend, so it is important that shippers determine the FAME content of diesel fuel cargoes. Where the FAME content of a diesel fuel cargo is not known it should be assumed to be 15 %.

Gas oil blends with bio-gas oil are also becoming more common and the same precautions should be applied to these products as for blended biodiesel.

Note 1: These comments also apply to FAME and other fatty acid esters.

Note 2: Some national specifications do not permit FAME in diesel which is not designated as biodiesel, even at contamination levels. In such cases precautions similar to those used for aviation jet fuel should be followed.

Note 3: Some gas oils may contain up to 2 000 ppm sulfur.

2.11.10 Ultra low sulfur automotive diesel fuel (and/or – ULSD, ULS turbine gas oil, LS marine gas oil, ULS diesel)

In addition to the comments in 2.11.9 these cargoes typically have a maximum sulfur content of 10 ppm (possibly 50 ppm depending on location). If they are to be loaded into tanks or through lines that have previously contained cargoes that had a greater sulfur specification, care should be taken to ensure that admixing is kept to a minimum.

These products are salt-water-critical as the specifications will not allow sodium or potassium. Fresh water washing and mopping may be specified.

Flashpoint may be critical such that admixing with low flashpoint cargoes in tanks and lines should be avoided.

2.11.11 Crude oil and condensate

The properties of crude oil cargoes vary considerably. General guidance, together with a list of physical properties of many grades, together with washing and carriage recommendations, is given in EI HM 40 *Guidelines for the crude oil washing of ships' tanks and the heating of crude oil being transported by sea*.

Condensate which is dark in colour may be treated as crude oil. However, some condensates are 'clean', i.e. not heavily coloured, and may be of sufficient quality to allow loading of clean products following a cold water wash, drain and mop (code 2M). However, clean condensate may contain wax which will require additional cleaning. Quality certificates should always be referenced for guidance.

When loading of aviation fuel is being considered, guidance should be sought from the cargo owner and attention should be given to all parameters of the condensate, in particular:

- ASTM D1500/IP 196 colour should be less than 2,5
- ASTM D86/IP 123 distillation should be less than 10 % residue at 280 °C
- Cloud point should be not greater than –10 °C
- Viscosity at 20 °C should be less than 1,5 cst

2.11.12 Base lubricating oils

The quality of lubricating oils is greatly affected by admixing with water and tank preparation will normally include mopping. Valves and strainers will also require opening and draining. To maintain quality and avoid introduction of water, lubricating oils should be loaded, carried and discharged under dry nitrogen and not dirty inert gas.

2.11.13 Vacuum gas oil (and/or – cracker feed, waxy distillate)

These cargoes are sodium-critical and tanks which have been salt water washed will require fresh water washing to remove any salt traces. Vacuum gas oil may be loaded on top of some light crude oils and condensates without washing. However, as with fuel oils, the need to heat the product leads to a high flashpoint specification and precludes admixing with any volatile residues.

2.11.14 Medium and heavy fuel oils

The admixing of these cargoes with waxy residues can result in the material not meeting the maximum pour point specification limit. Tanks which have carried high pour point cargoes should be carefully drained and stripped prior to loading.

The need to heat the product leads to a high flashpoint specification and precludes admixing with any volatile residues. Washing will generally be required when loading these products after crude oil cargoes.

2.11.15 Low sulfur fuel oil (and/or – low sulfur atmospheric residue (LSAR), low sulfur waxy residue (LSWR))

In addition to comments in 2.11.14, these products are frequently traded with sulfur content very close to the specified upper limit. Admixing with cargoes with higher sulfur content should therefore be kept to a minimum. Hot washing may be required when loading after crude oils or other fuel oils, depending on the characteristics of the cargo discharged.

Cargoes for refinery cracking will also be sodium-critical and tanks which have been salt water washed will require washing with fresh water to remove any salt traces.

2.11.16 Light fuel oil

The admixing of these cargoes with waxy residues can result in the material not meeting the maximum viscosity and/or pour point specification limit. Tanks which have carried high pour point or high viscosity fuel oil or crude oil should be hot washed at the highest permitted temperature to remove wax traces. The need to heat the product leads to a high flashpoint specification and precludes admixing with any volatile residues.

Washing may be avoided if a previous cargo of heavier grade fuel oil has low wax content and the amount ROB is minimal (less than 0,1 % of volume).

2.11.17 Gas to liquids (GTL) products

A number of GTL products are entering the market: typically naphtha, kerosenes and diesel. Properties are as per similar non-GTL cargoes but all are low sulfur and low aromatic and should be handled accordingly.

2.11.18 FAME and blended biodiesel

FAMEs vary considerably in properties, depending on the original source of the oil/fat. However, all are prone to absorb water both from the atmosphere and from tank washing activities. Tanks which have been subject to water washing should therefore be mopped dry before loading any cargo of FAME or FAME/petroleum diesel blend.

2.11.19 Light cycle oil (LCO)

LCO can be a dark or clear, straw-coloured product.

With regard to products following LCO: dark LCO should be treated as a black oil cargo and clear LCO can be treated as gas oil.

Cleaning before loading LCO will depend on the end use of the product and, of course, the previous cargo. Advice should be requested from the cargo owner/charterer.

Table 1: Tank cleaning recommendations

This Table to be used only with reference to the written recommendations of HM 50. See 2.11

This Table to be used only with reference to the written recommendations of HM 50. See:	Cargo to be loaded	Previous Cargo																								
		Aviation gasoline	Wide cut jet fuel, JP4, Jet B	Aviation jet fuel and components	Motor gasoline containing oxygenates (ethanol, MTBE, etc.)	Motor gasoline (unleaded)	Ultra low sulfur motor gasoline (unleaded)	Motor gasoline (leaded)	Naphtha (lead-free)	Natural gasoline (NGLs)	Kerosene (undyed)	Kerosene (dyed)	Gas oil (undyed)	Gas oil (dyed)	Ultra low sulfur gas oil/diesel	Diesel blended with up to 5 % FAME (B5 or lower) (see note 4)	Diesel blended with 5 % to 15 % FAME (B15 or lower) (see note 4)	FAME or diesel/gas oil blended >15 % FAME (B15 or higher) (see note 4)	Solvents	White spirit	Base lubricating oil	Vacuum gas oil	Fuel oil (sulfur < 1 %)	Low sulfur fuel oil (sulfur < 1 %)	Crude oil and condensate (see note 6)	
2.11.2	Aviation gasoline #	1	2	2	1	1	1	1	2M	2M	2M	2M	2M	2M	2M	3M*	X*	X*	2M	2M	X*	X*	X*	X*	X*	X*
2.11.2	Wide cut jet fuel, JP4, Jet B #	2M	1	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	3M*	X*	X*	2M	2M	X*	X*	X*	X*	X*	X*
2.11.7	Aviation jet fuel and components #	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	3M*	X*	X*	2M	2M	X*	X*	X*	X*	X*	X*
2.11.4	Motor gasoline (unleaded) containing oxygenates (ethanol, MTBE, etc.)	2M	1	1	1	1	1	1	2M	1	1	1	1	1	1	1	2M	2M	2	2	3M	3M	3M	3M	3M	X
2.11.4	Motor gasoline (unleaded) †	2	1	1	1	1	1	1	2M	2M	2M	2M	2M	2M	2M	1	2	2	2	2	3	3	3	3	3	X
2.11.5	Ultra low sulfur motor gasoline (unleaded) †	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	1	1	1	3M	3M	X	X	X	X	X	X
2.11.3	Motor gasoline (leaded) †	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	3	3	3	3	3	X
2.11.1	Naphtha (lead-free) † #	X	1	2 See Note 8	1	1	1	1	X	1	1	1	1	1	1	2	3	3	1	1	3	3	3	3	3	X
2.11.1	Natural gasoline (NGLs) †	X	1	1	1	1	1	1	X	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	X
2.11.8	Kerosene (undyed)	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2	2	2	2	2	2	2	X
2.11.8	Kerosene (dyed)	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2	2	2	2	2	2	2	X
2.11.9	Gas oil (undyed)	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2	2	2	2	2	2	2	X
2.11.9	Gas oil (dyed)	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2	2	2	2	2	2	2	X
2.11.10	Ultra low sulfur gas oil/diesel	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	3M	3M	X	X	X	X	X
2.11.6	Solvents † # and white spirit	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2	2	X	X	X	X	X	X
2.11.12	Base lubricating oil	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	2M	3M	3M	LU	X	X	X	X	X
2.11.13	Vacuum gas oil #	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	3P
2.11.14	Fuel oil (sulfur > 1 %)	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	3P
2.11.15	Low sulfur fuel oil (sulfur < 1 %)	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	2P	3P
2.11.11	Crude oil, condensate †	2	1	1	1	1	1	1	2	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

Table 1: Tank cleaning recommendations (continued)

Code	Cleaning recommendations
X	Not to be loaded without special cleaning instructions
X*	Not to be loaded without special cleaning instructions. Three clean and zero biological content intermediate cargoes recommended
1	Drain tanks, lines and pumps well. If previous cargo shows signs of instability or oxidation (dark colouring or broken down from sediment) then use code 2M
2	Wash with cold water and drain well
3	Wash with hot water and drain well
3M*	A stringent hot water wash, drain and mop may be sufficient if tanks are in good condition. As an alternative one clean product/zero biological content intermediate cargo is recommended, followed by hot water wash, drain and mop. Fresh water rinse required if sea water is used. Consideration may be given to substituting mopping by enhanced stripping and drying, see 2.10
P	Purge to below 2 % hydrocarbon by volume
M	Gas-free, lift scale and mop. Consideration may be given to substituting mopping by enhanced stripping and drying, see 2.10
#	Fresh water rinse after any salt water wash when loading these products
LU	Reduced cleaning may be permitted depending on Lubricating Oil Specification. Otherwise apply code 3M
Notes:	<ol style="list-style-type: none"> 1. Additional cleaning may be required for uncoated tanks, tanks with extensive coating breakdown or where specified by the charter party 2. † Benzene may be present in any petroleum product but may be present in higher concentrations in those products marked †. Refer to ISGOTT for precautions in handling cargo suspected of having a benzene content and prior to entering a space which has contained such a cargo 3. In cases where the FAME content in diesel is unknown, and in locations where reporting of FAME content is not required, it shall be assumed to be 15 % 4. Comments regarding FAME also apply to FAEE and other fatty acid esters 5. Where high sulfur kerosene or gas oil has been discharged Code 2 should be used 6. Refer to quality certificate: some condensates are of sufficient quality as to allow loading of clean products, including aviation fuel, following cleaning to code 2M 7. Lubricating oil should be loaded, carried and discharged under air or nitrogen only 8. Chemical grade naphtha is very sensitive to contamination by oxygenates. Stringent cleaning is required before loading this product. Some contracts require three oxygenate-free cargoes before loading chemical grade naphtha

ANNEX A

GLOSSARY OF TERMS

For the purposes of these EI guidelines, the terms used should be understood to have the following meanings:

admixture; transmix	Quantity of a different product (usually from a previous batch or cargo) which becomes mixed with the current batch or cargo.
ATK	Aviation turbine kerosene.
aviation jet fuel:	
conventional	Hydrocarbons for use in aviation turbine engines and derived from the following conventional sources: crude oil, natural gas, liquid condensate, heavy oil, shale oil and oil sands.
synthetic	Hydrocarbons for use in aviation turbine engines and derived from alternative sources such as coal, natural gas, biomass and hydrogenated fats and oil by processes such as gasification, Fisher-Tropsch synthesis and hydroprocessing.
ballast	Water taken on board when a vessel is empty or partially loaded/discharged to increase draught so that the propeller is fully immersed, stability and trim are maintained, and stresses minimised.
black oils	Petroleum products containing residual components which make them dark in colour.
blended biodiesel	Diesel fuel which is a blend of biologically-derived components (e.g. FAME, FAEE or other fatty acid esters), and petroleum diesel. The percentage of biological component is often designated in the grade name, e.g. B15 indicates 15 % biological component.
blended bio-gas oil	Gas oil which is a blend of biologically-derived components (e.g. FAME, FAEE or other fatty acid esters), and petroleum gas oil.
bottom wash	Washing operations restricted to the lower parts of the tank bulkheads, internal structures and bottom of tanks. This can only be carried out by vessels equipped with programmable tank washing machines.
clean ballast	Ballast contained in cargo tanks that have been COW'd (where appropriate) and thoroughly water washed. It may be discharged to sea and meets MARPOL requirements.
clingage	Material which adheres to the surfaces of tank walls and structures, both horizontal and vertical, within empty and part empty tanks, other than bottom surfaces.
crude oil washing (COW)	The use of a high pressure stream of the crude oil cargo to dislodge or dissolve clingage and sediments from the bulkheads, bottom, and internal tank structures of a vessel during the discharge operation.

fatty acid ethyl ester (FAEE)	Sometimes referred to as biodiesel or B100 (not yet widely used but properties similar to FAME).
fatty acid methyl ester (FAME)	Sometimes referred to as biodiesel or B100.
flashpoint	Lowest temperature of the test portion, corrected to a barometric pressure of 101,3 kPa, at which the application of an ignition source causes the vapour of the test portion to ignite and the flame to propagate across the surface of the liquid under the specified conditions of test.
full cycle washing	Washing operation in which the complete cargo tank is washed, either by programmable or non-programmable machines.
gas-free	A tank, compartment or container is gas-free when sufficient fresh air has been introduced into it to lower the level of any flammable, toxic, or inert gas to that required for a specific purpose, e.g. hot work, entry, etc.
IMO	International Maritime Organization.
inert gas (IG)	A gas or gas mixture used to render the vapour space in the cargo tank non-flammable.
ISGINTT	International Safety Guide for Inland Navigation Tank-barges and Terminals.
ISGOTT	International Safety Guide for Oil Tankers and Terminals.
ISO	International Organization for Standardization.
MARPOL	Latest version of the Protocol of 1978 relating to the International Convention for the Prevention of Pollution from Ships, 1973.
oxygenate	An oxygen-containing organic compound such as an alcohol (e.g. ethanol), or ether (e.g. MTBE, ETBE) that can be used as a gasoline component.
persistent oil	The International Oil Pollution Compensation (IOPC) Fund guidelines consider an oil as non-persistent if, at time of shipment, at least 50 % of the hydrocarbon fractions, by volume, distil at a temperature of 340 °C and at least 95 % of the hydrocarbon fractions, by volume, distil at a temperature of 370 °C when tested in accordance with ASTM D86. A persistent oil is one which does not meet these criteria.
pour point	The lowest temperature at which a sample of petroleum product will continue to flow when it is cooled under specified standard conditions (see IP 15/ASTM D 97).
purging	The introduction of inert gas into a tank already in an inert condition with the object of further reducing the existing oxygen content and/or the existing gas content to a level below which combustion cannot be supported if air is subsequently introduced into a tank.
remaining on board (ROB)	Sum of measured liquid volume, including free water, and measured non-liquid volume but excluding vapours, in cargo tanks on completion of discharge.

saponifier	A solution of organic or inorganic bases (alkalines, e.g. caustic soda), and various agents, such as wetting agents and dispersants, which react with, and promote the removal of, non-water-soluble contaminants, such as vegetable oils.
segregated ballast tankers (SBTs)	Vessels having sufficient dedicated ballast tanks to enable safe seagoing operations under normal weather conditions.
slop tank(s)	For the purposes of these guidelines tank(s) utilised as a reservoir for COW medium and receipt of tank washings.
SOLAS	International Convention for the Safety of Life at Sea.
stripping	The removal of the final contents of a cargo tank, possibly using equipment additional to the main cargo pumps.
trim	The difference between the fore and aft draught of the vessel. When the aft draught is greater than the forward draught, the vessel is said to be trimmed 'by the stern'. When the aft draught is less than the forward draught, the vessel is said to be trimmed 'by the head'.
true vapour pressure (TVP)	The absolute pressure exerted by the gas produced by evaporation from a liquid, when the gas and liquid are in equilibrium at the prevailing temperature.
viscosity	A measurement of a fluid's resistance to flow at a prescribed temperature. In this document the unit of Kinematic Viscosity, the centistoke (cSt) has been used, which is equivalent to mm ² /s.
wax	A mixture of long chain hydrocarbons that crystallise at different temperatures as the overall fluid temperature falls.
white oils	Clean, refined petroleum products which are not dark in colour such as motor spirit, kerosene, gas oil, diesel fuel and blending components.

ANNEX B

REFERENCES

The following standards and papers have been used in the preparation of this publication:

Central Commission for Navigation on the Rhine (CCNR) – <http://www.eda.admin.ch/smno/en/home/zentralkommission-fuer-die-rheinschiffahrt.html>

Oil Companies International Marine Forum (OCIMF) – <https://www.ocimf.org>

International safety guide for inland navigation tank-barges and terminals

Energy Institute (EI) – <https://www.energyinst.org>

EI/JIG 1530 Quality assurance requirements for the manufacture, storage and distribution of aviation fuels to airports

HM 40 Guidelines for the crude oil washing of ships' tanks and the heating of crude oil being transported by sea

International Maritime Organization (IMO) – <https://www.imo.org>

Crude oil washing systems, revised 1983

International Convention for the Safety of Life at Sea (SOLAS), 1974, including amendments, Chapters 11 and 12

Regulations for the prevention of pollution by oil, Annex 1 and Annex II of MARPOL 73/78 including amendments

Witherbys – <http://www.witherbys.com>


International Safety Guide for Oil Tankers and Terminals, 5th edition



Energy Institute
61 New Cavendish Street
London W1G 7AR, UK

t: +44 (0) 20 7467 7100
e: pubs@energyinst.org
www.energyinst.org

This publication has been produced as a result of work carried out within the Technical Team of the Energy Institute (EI), funded by the EI's Technical Partners and other stakeholders. The EI's Technical Work Programme provides industry with cost effective, value adding knowledge on key current and future issues affecting those operating in the energy industry.



9780852939826

ISBN 978 0 85293 982 6

Registered Charity Number: 1097899